



Ethanol Production Pumps



Experience In Motion



The Most Trusted in the Industry

Flowserve has been successfully providing equipment for the corn processing and ethanol production industry for more than 35 years. Its reputation is built upon superior pump design, unequalled materials expertise and field-proven performance.

Ethanol Pumping Expertise

- Mash
- Evaporation
- Beer bottoms
- Final ethanol
- Acid wash
- Gasoline
- Boiler feed
- Fermentation/beer
- Process condensate
- Product
- CIP
- Cooling water
- Sump
- Milling/steeping

Superior Product Design

With ideal design features for abrasive and corrosive services, Flowserve ANSI and ISO process pumps are the global workhorses of ethanol production.

- Mark 3 ANSI reverse vane impeller transfers erosion/corrosion from casing to less expensive rear cover; repeatable “as new” performance after wear and impeller adjustment; low NPSHR
- CPX ISO precision cast semi-open impeller delivers high efficiency, low NPSHR
- Tapered bore seal chamber with flow modifiers permits less costly sealing arrangement due to self-venting and solids-handling capabilities
- Heavy-duty power end with lifetime warranty gives full protection during hose down
- Reinforced baseplate options



Materials Expertise

Many ethanol production pump users standardize on ASTM A995, grade CD4MCuN. Invented by Flowserve, this duplex stainless steel has a hardness approximately three times that of austenitic stainless steels. It also has greater pitting and crevice corrosion resistance compared with other duplex stainless steels or 316SS.


Other materials include:

- ASTM A995, grade CD4MCuN with hard coating
- CR29 hard chrome cast iron (>500 Brinell)
- ASTM A744, grade CN7M (Alloy 20)
- ASTM A744, grade CF8M (316SS)
- ASTM A395, grade 60-40-18 (DCI)
- Fluoropolymer

In addition to standard shaft materials, Flowserve offers two highly corrosion and abrasion resistant proprietary alloys.

These include:

- DC8, a cobalt-based alloy with appreciable amounts of chromium and molybdenum
- SD77 high silicon iron



Industry Leading Ethanol Production Pumps

- Starch Conversion
- Fermentation
- Distillation
- Storage
- Stillage Handling

Standard Process Pumps

Mark 3 (ANSI B73.1), CPX (ISO 2858/5199)

- ● ● ● ● ● - Standard
- ● ● ● ● ● - Recessed impeller
- ● ● ● ● ● - Self-priming
- ● ● ● ● ● - Dynamically sealed

Fluoropolymer Lined Pumps

- ● ● ● ● ● - PolyChem™ S-Series (ANSI B73.1 and ISO 2858)

Heavy-duty (Stock) Pumps

- ● ● ● ● ● - FRBH
- ● ● ● ● ● - Mark 3, Group 3 and 4

Sealless Pumps


- ● ● ● ● ● - Magnetic drive-metallic
 - Guardian® (ANSI B73.1)
 - CPXS (ISO 2858/5199)
- ● ● ● ● ● - Magnetic drive-fluoropolymer lined
 - PolyChem M-Series (ANSI B73.1 and ISO 2858)


Cooling Water and Sump Pumps

- ● ● ● ● ● - VTP vertical turbine
- ● ● ● ● ● - LR and LNN axially split, single stage
- ● ● ● ● ● - Standard and cantilever sump pumps
- ● ● ● ● ● - MDX vertical submersible, formed SS

Boiler Feed Pumps

- ● ● ● ● ● - Radially split, multistage ring section





USA and Canada

Flowserve Corporation
5215 North O'Connor Blvd.
Suite 2300
Irving, Texas 75039-5421 USA
Telephone: 1 972 443 6500
Telefax: 1 972 443 6800

Europe, Middle East, Africa

Flowserve Corporation
Via Rossini 90/92
20033 Desio (Milan), Italy
Telephone: 39 0362 6121
Telefax: 39 0362 303396

Latin America and Caribbean

Flowserve Corporation
6840 Wynnwood Lane
Houston, Texas 77008 USA
Telephone: 1 713 803 4434
Telefax: 1 713 803 4497

Asia Pacific

Flowserve Pte. Ltd.
200 Pandan Loop #06-03/04
Pantech 21
Singapore 128388
Telephone: 65 6775 3003
Telefax: 65 6779 4607

Bulletin FPD-14[†] (E) Printed in USA. August 2006. © Flowserve Corporation

To find your local Flowserve representative:

For more information about Flowserve Corporation,
visit www.flowserve.com or call USA 1 800 728 PUMP (7867)