

Synthetic Blend Rotary Screw Air Compressor Oil DMS-4

Product Description

DMS-4 is a custom blended polyalphaolefin (PAO) partial synthetic hydrocarbon oil giving improved lubrication at high and low temperatures, reduced volatility, good chemical inertness and hydrolytic stability, and compatibility with mineral oils and equipment designed for use with mineral oils. It is a long life lubricant formulated for, and designed to replace, mineral oils in flooded rotary screw air compressors.

DMS-4 is nontoxic and carries no hazardous labels or warnings under the OSHA Right to Know Law 29 CFR 1910.1200.

Typical Applications

Rotary screw air compressors

Typical Properties*

.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
Viscosity				
@ 40°C cSt per ASTM D445	40.3			
@ 100°C cSt	6.4			
@ 100°F SUS	210			
@ 210°F SUS	47.5			
Viscosity Index, per ASTMD 2270	108			
Flash Point, C.O.C., °F (°C) per ASTM D92	450 (232)			
Fire Point, C.O.C., °F (°C) per ASTM D92	495 (257)			
Pour Point, °F (°C) per ASTM D97	<-35 (<-37)			
Density lb./gal. 60°F (15°C)	7.12			
Specific Gravity @ 72°F per ASTM D1298 0.85				
*These values are not intended for use in preparing specifications.				

The information and specifications presented in this product brochure are believed to be accurate, but are supplied for information purposes only and should not be considered certified or as a guarantee of satisfactory results by reliance thereon. Nothing contained herein is to be construed as a warranty or guarantee, express or implied, with respect to the product. Although Flowserve Corporation can provide general application guidelines, it cannot provide specific information for all possible applications. The purchaser/user must therefore assume the ultimate responsibility for the proper selection, installation, operation and maintenance of Flowserve products. Because Flowserve Corporation is continually improving and upgrading its product design, the specifications, dimensions and information contained herein are subject to change without notice.

Primary Worldwide Flow Solutions Division Locations

				Licensees, authorized ager	
United States		Canada		Netherlands	
Kalamazoo, MI Phone 616-381-2650 Fax 616-381-8368	Temecula, CA Phone 909-676-5662 Fax 909-308-4495	Edmonton, Alberta Phone 708-463-7958 Fax 708-450-1241	Scarborough, Ontario Phone 416-292-2877 Fax 416-292-5190	Roosendaal Phone 31-165-581-400 Fax 31-165-552-622	Me Ph Fax
Singapore	Mexico	Brazil	Japan	Germany	
Phone 65-746-4318 Fax 65-747-1963	Tlaxcala Phone 52-2-461-6791 Fax 52-2-461-6847	Sao Paulo Phone 55-11-4066-8600 Fax 55-11-4066-7014	Osaka Phone 81-720-85-5571 Fax 81-720-85-5575	Dortmund Phone 49-231-6964-0 Fax 49-231-6964-248	Ma Ph Fax
			100 0000		

Licensees, authorized agents, and affiliated companies located worldwide

Argentina Vendoza Phone 54-261-427-2300 ax 54-261-427-2524

Australia Marayong NSW Phone 61-2-8822-7100 ax 61-2-9679-7511

www.flowserve.com

REV 02/97 USA Printed In USA

© Copyright 1999 Flowserve Corporation



Certified